




SkyHawk M-type Module Specification

Monocrystalline 6X18 Solar Modules for Salt Field Type

182mm / M10 Solar Cell

405Wp / 410Wp



The highest Mechanical Load Test in PV Industry



Better LCOE



Improved module power output performance by reducing module working temperature



Advanced Non-Destructive Cutting Technology



World's best PID resistant



Multi Busbar Technology



The toughest Salt Mist Test in PV Industry

Green Energy

Made in Taiwan



Sustainable Development



SkyHawk M-type Module Specification(182mm / M10 Solar Cell)

Monocrystalline 6X18 Solar Modules for Salt Field Type

390-420Wp



Electrial Data

Model Name			TS54-BMH-390 H1	TS54-BMH-395 H1	TS54-BMH-400 H1	TS54-BMH-405 H1	TS54-BMH-410 H1	TS54-BMH-415 H1	TS54-BMH-420 H1
Max. power at STC	P _{max}	W	390	395	400	405	410	415	420
Max. power voltage	V _{mp}	V	30.22	30.32	30.42	30.52	30.62	30.72	30.82
Max. power current	I _{mp}	A	12.91	13.03	13.15	13.27	13.39	13.51	13.63
Open circuit voltage	V _{oc}	V	36.82	36.90	36.98	37.06	37.14	37.22	37.3
Short circuit current	I _{sc}	A	13.64	13.71	13.78	13.85	13.92	13.99	14.06
Module Conversion Eff.	%		20.0%	20.2%	20.5%	20.8%	21.0%	21.3%	21.5%

* Under Standard Test Condition(1,000W/m²,25°C,AM 1.5): Power Tolerance ±3%, Voc Tolerance ±3%, Isc Tolerance ±3%
* Module Conversion Eff. (%) = [Max power at STC(w) / ((Solar Module Area(m²) x 1000 (w/m²))] x 100%

Temperature Coefficient

Nominal Operating	NOCT	°C	45±2
Cell Temperature			
TC Isc	α	%/ °C	+0.06
TC Voc	β	%/ °C	- 0.27
TC Pmax	γ	%/ °C	- 0.35

Operation Conditions


Max. system voltage	1500V
Module fire resistance class	Class C
Protection Class (IEC 61140)	Class II
Series fuse rating	25 A
Number of bypass diodes	3
Temperature range	-40 to +85°C
Max. mechanical load	7100 pa(front side) 5400 Pa(rear side)

* Please follow installation manual provided by TSEC


General Data

Cell type	M10 Monocrystalline
Cell per module	Mono-crystalline silicon solar cell (108 pcs)
Front	Low-iron tempered glass
Encapsulant Flim	Low water vapor transmission rate (WVTR) material
Rear	Anti-Salt Mist composite film
Frame	Anti-Salt Mist aluminum (silver/black)
Junction Box	IP68
Connector	EVO-2 Compatible
Cable	1500mm / 4mm ²

IV Curve



Engineering Drawing(mm)




Certifications

- IEC 61215:2016 、 IEC 61730-1:2016 & IEC 61730-2:2016
- ISO 9001:2015 Quality management system
- ISO 14001:2015 Environmental management system
- ISO 45001:2018 Occupational health and safety management system



% Warranted Power



Warranty

- 12-year materials and workmanship warranty
- 25-year linear power warranty

Made in Taiwan

* The information in this document is subject to change without notice

* TSEC reserves the rights of final interpretation and revision of datasheet

* Version : Rev.7, April 2025

TSEC Corporation

Taipei Headquarters | 8F., No.225, Sec3, Beixin Rd., Xindian Dist., New Taipei City 23143, Taiwan, R.O.C

T +886-2-2912-2199 F +886-2-2917-5399 M international.sales@tsecpv.com(Sales Contact) epc@tsecpv.com(EPC Construction Service)