

## SkyHawk R-type Module Specification

Monocrystalline 6X22 Solar Modules for Rooftop Type

182mm / M10 Solar Cell

# 480~515Wp



The highest Mechanical Load Test in PV Industry



Better LCOE



Improved module power output performance by reducing module working temperature




Advanced Non-Destructive Cutting Technology



World's best PID resistant



Multi Busbar Technology



The toughest Salt Mist Test in PV Industry

Green Energy

Made in Taiwan



Sustainable Development



# SkyHawk R-type Module Specification(182mm / M10 Solar Cell) Monocrystalline 6X22 Solar Modules for Rooftop Type 480-515Wp



## Electrial Data

Model Name	TS66-BMH-480 H1	TS66-BMH-485 H1	TS66-BMH-490 H1	TS66-BMH-495 H1	TS66-BMH-500 H1	TS66-BMH-505 H1	TS66-BMH-510 H1	TS66-BMH-515 H1		
Max. power at STC	Pmax	W	480	485	490	495	500	505	510	515
Max. power voltage	Vmp	V	37.78	37.93	38.08	38.23	38.38	38.53	38.68	38.93
Max. power current	Imp	A	12.71	12.79	12.87	12.95	13.03	13.11	13.19	13.27
Open circuit voltage	Voc	V	44.95	45.10	45.25	45.40	45.55	45.70	45.85	46.00
Short circuit current	Isc	A	13.59	13.67	13.74	13.82	13.90	13.97	14.04	14.11
Module Conversion Eff.	%		20.3%	20.5%	20.7%	20.9%	21.1%	21.3%	21.5%	21.7%

\* Under Standard Test Condition(1,000W/m<sup>2</sup>,25°C,AM 1.5): Power Tolerance ±3%  
\* Module Conversion Eff. (%) = [Max power at STC(w) / ((Solar Module Area(m<sup>2</sup>)) x 1000 (w/m<sup>2</sup>))] x 100%

### Temperature Coefficient

Nominal Operating	NOCT	°C	45±2
Cell Temperature			
TC Isc	α	%/°C	+0.06
TC Voc	β	%/°C	- 0.27
TC Pmax	γ	%/°C	- 0.35



### Operation Conditions

Max. system voltage	1500V
Module fire resistance class	Class C
Protection Class (IEC 61140)	Class II
Series fuse rating	25 A
Number of bypass diodes	3
Temperature range	-40 to +85°C
Max. mechanical load	7100 pa(front side) 5400 Pa(rear side)

\* Please follow installation manual provided by TSEC

### General Data


Cell type	M10 Monocrystalline
Cell per module	Mono-crystalline silicon solar cell (132 pcs)
Front	Low-iron tempered glass
Encapsulant Film	Ethylene Vinyl Acetate(EVA)
Rear	Composite film
Frame	Anti-Salt Mist aluminum (silver/black)
Junction Box	IP68
Connector	EVO-2 Compatible
Cable	1500mm / 4mm <sup>2</sup>



### Module Dimensions and Weight

Dimension	2092 x 1133 x 40 mm
Weight	26 Kg

- ### Certifications
- IEC 61215:2016、IEC 61730-1:2016 & IEC 61730-2:2016
  - ISO 9001:2015 Quality management system
  - ISO 14001:2015 Environmental management system
  - ISO 45001:2018 Occupational health and safety management system



**Made in Taiwan** \* The information in this document is subject to change without notice \* TSEC reserves the rights of final interpretation and revision of datasheet \* Version : Rev.5, September 2023